



LAPPATO PORCELAIN TILES



WHAT IT'S FOR

- Protects surfaces from dirt caused by heavy foot traffic.
- Restores and increases the material surface's sheen.
- Makes regular maintenance of lappato porcelain tiles easier.
- After 24 hours of applying FILAPD15 the protection reaches maximum effectiveness.

ADVANTAGES

- Safe on all kinds of lappato porcelain tiles.
- The protection does not form a film and allows the surface to breath.
- Protection is permanent with no need for further application of the product.
- Ready to use.
- Highly resistant to traffic and maintenance cleaning.
- The sentence is on the sheet twice.
- Does not yellow, UV resistant, and it has high coverage. .
- The product becomes an integral part of the material without altering its appearance.
(Min. Dec. No. 236 of 14/06/1989 and ASTM C 1028-2007).

HOW IT'S USED

No dilution required: ready to use.

Application for new installations:

1. Wash the floor thoroughly using **DETERDEK** cement grout remover or **FILACR10** epoxy grout remover.
2. with the surface clean and dry, apply **FILAPD15** evenly on the surface (including grout joints) using a brush, sponge or lamb wool applicator.
3. Rub the surface with a cloth, paper towel, or single disc machine with white pad to help with product penetration.
3. Remove any residue within 10 minutes, using a clean cotton cloth or single-disc machine fitted with a white pad. We recommend applying this product on 2-3 m² (21.52 sq ft to 32.28 sq ft) at a time.
4. The surface is ready for use after 8 hours.

Application on untreated surface to be restored:

1. Wash the floor using **FILAPS87** and/or **DETERDEK**.
2. Apply **FILAPD15** on the dry surface in the manner described above.

Suggestion:

In case of stubborn residues, rub the surface with a cloth wetted with the product until they disappear completely.

Caution: *It may enhance the color of the material and/or grout, carry out a spot test beforehand to check for any changes in color.*

COVERAGE

With one litre (1,06 QT):

Lappato porcelain tiles

70 m² (753 sq ft)

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 liter (1.06 qt) flasks in box of 6.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Solvent based: when used indoors, ventilate premises thoroughly. Keep in a cool, dry place.
- Don't apply the product if it could rain within 8 hours.

COMPOSITION

A mixture of siloxanic compounds dispersed in de-aromatised hydrocarbon solvent.

TEMPERATURE

Storage temperature:

between 32° F (0° C) and 86° F (30° C).
Must be applied to material at temperatures between 41° F (5° C) and 86° F (30° C).

LABELLING

DANGER! HARMFUL OR FATAL IF SWALLOWED.
FLAMMABLE.

Contains petroleum distillates. Avoid frequent or prolonged contact with skin. Do not use near heat or open flame. If swallowed, call a poison control center, physician or emergency room immediately. Keep out of reach of children.

TECHNICAL INFORMATION

Appearance: liquid

Color: colourless

Odour: typical of hydrocarbon solvent

Density: 0.978 kg/l

Flash point: 104° F

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.