

FILASTOP DIRT

PROTECTIVE BARRIER AGAINST DIRT



- TEXTURED PORCELAIN TILES
- UNPOLISHED PORCELAIN TILES
- LAPPATO PORCELAIN TILES



PICTURES: by courtesy of Ceramiche Atlas Concorde S.p.a.

WHAT IT'S FOR

- Improves the material's resistance to dirt caused by traffic.
- Protects the material against watery or oily stains.
- Facilitates cleaning of the surfaces.

ADVANTAGES

- The product bonds chemically with the material without leaving a film on the surface.
- Limits water retention (laboratory tests conducted on floors laid according to the **UNI 11493 standard**).
- Does not modify the degree of slipperiness of the material (tests conducted in conformity to the **B.C.R.A. and ASTM C 1028-2007 methods**).
- Suitable for interior and outdoor use.
- Resists UV radiation and does not yellow.

COVERAGE

With one litre (1,06 QT):

Textured and unpolished porcelain
30-40 m² (322 sq ft – 430 sq ft)

"Coverage rates are approximate and refer to a single coat of the product"

HOW IT'S USED

Product is ready to use: no dilution required.

Application:

We recommend applying the product to 2-3 m² (20-30 sq. ft.) area at a time. To a clean and dry surface, apply **FILASTOP DIRT** with a paintbrush, or lambswool applicator pad. After 10 minutes, remove the excess residues that have not been absorbed, by using a dry cloth, lambswool applicator pad, or sponge. In the case of stubborn residues, rub the surface with a cloth soaked in the product until residues are completely removed. Process can be finished with a single-disc machine using white pad, or by hand using a dry cloth, or paper towels to thoroughly dry the surface. The surface can be walked on after 12 hours.

Caution:

Do not apply externally if rain is in forecast.

Warning:

Before using the product, we recommend carrying out a spot test to check for any changes in color, since product may enhance the color of the material, and or grout. Air the room during use to speed up drying process.

Packaging

1 liter (1,06 QT) cans in box of 6.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- To be treated, an external floor has to be laid perfectly, and respond to every requirement as, for example: the respect of slopes, the correct construction of joints, the perfect isolation of the floor and the tested frost resistance of the material.
- Doesn't protect marble and calcareous stone from acid aggression.
- Use a single-disc professional cleaner only if the machine is intact in all its parts

TEMPERATURE

Storage temperature:
between 32° F (0° C) and 86° F (30° C).
Must be applied to material at temperatures
between 41° F (5° C) and 86° F (30° C).

LABELLING

CAUTION! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

Causes irritation to skin and eyes. Vapors irritating and harmful. Contains petroleum distillates. Avoid prolonged contact with skin. Do not get in eyes. Do not swallow. Use with adequate ventilation. Avoid flames and sources of combustion. Keep out of the reach of children. FIRST AID: In case of eye contact, flush with running water for up to 15 minutes and get medical assistance. SKIN: Flush with running water and get medical aid for irritation or any other symptom. IF SWALLOWED: Call a physician or poison control center. Inhalation: Remove to fresh air. Get medical assistance for any symptom. WARNING: Contains materials known to the State of California to cause reproductive toxicity.

TECHNICAL INFORMATION

Appearance: liquid
Color: colorless
Odour: slight odour of hydrocarbon solvent
Density: 0.887 kg/liter
Flash point: 104° F

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.